

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.03.2024

Version number 2.0 (replaces version 1.0)

Revision: 11.03.2024

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** Mr. RAPID THINNER
- **Article number:** T-117
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
GSI EUROPE - Import + Export GmbH
Louise-Dumont-Str. 31
40211 DÜSSELDORF
GERMANY
- **Further information obtainable from:** Hobby Department
- **Emergency telephone number:** During normal opening times: +49/211/1665 98420

2 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

Carc. 2 H351 Suspected of causing cancer.



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.03.2024

Version number 2.0 (replaces version 1.0)

Revision: 11.03.2024

Trade name: Mr. RAPID THINNER

(Contd. of page 1)

· **Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS02 GHS05 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

4-methylpentan-2-one

butan-1-ol

2-butoxyethanol

butanone

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H351 Suspected of causing cancer.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

GB

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.03.2024

Version number 2.0 (replaces version 1.0)

Revision: 11.03.2024

Trade name: Mr. RAPID THINNER

(Contd. of page 2)

3 Composition/information on ingredients

• **Mixtures**

• **Description:** Mixture of substances listed below with nonhazardous additions.

• **Dangerous components:**

CAS: 78-93-3 EINECS: 201-159-0	butanone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	>25–≤50%
CAS: 108-10-1 EINECS: 203-550-1	4-methylpentan-2-one ⚠ Flam. Liq. 2, H225; ⚠ Carc. 2, H351; ⚠ Acute Tox. 4, H332; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 ATE: LC50/4 h inhalative: 11 mg/l	>25–≤50%
CAS: 71-36-3 EINECS: 200-751-6	butan-1-ol ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	≥20–≤25%
CAS: 64-17-5 EINECS: 200-578-6	ethanol ⚠ Flam. Liq. 2, H225	>2.5–≤10%
CAS: 111-76-2 EINECS: 203-905-0	2-butoxyethanol ⚠ Acute Tox. 3, H311; ⚠ Acute Tox. 3, H331; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE: LD50 oral: 1,200 mg/kg LC50/4 h inhalative: 3 mg/l	>2.5–<10%

• **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

• **Description of first aid measures**

• **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

• **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

• **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

• **After swallowing:** If symptoms persist consult doctor.

• **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.03.2024

Version number 2.0 (replaces version 1.0)

Revision: 11.03.2024

Trade name: Mr. RAPID THINNER

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.03.2024

Version number 2.0 (replaces version 1.0)

Revision: 11.03.2024

Trade name: Mr. RAPID THINNER

(Contd. of page 4)

- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

78-93-3 butanone

WEL	Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Sk, BMGV
-----	---

108-10-1 4-methylpentan-2-one

WEL	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm Sk, BMGV
-----	--

71-36-3 butan-1-ol

WEL	Short-term value: 154 mg/m ³ , 50 ppm Sk
-----	--

64-17-5 ethanol

WEL	Long-term value: 1920 mg/m ³ , 1000 ppm
-----	--

111-76-2 2-butoxyethanol

WEL	Short-term value: 246 mg/m ³ , 50 ppm Long-term value: 123 mg/m ³ , 25 ppm Sk, BMGV
-----	---

· **Ingredients with biological limit values:**

78-93-3 butanone

BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one
------	---

108-10-1 4-methylpentan-2-one

BMGV	20 µmol/L Medium: urine Sampling time: post shift Parameter: 4-methylpentan-2-one
------	--

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.03.2024

Version number 2.0 (replaces version 1.0)

Revision: 11.03.2024

Trade name: Mr. RAPID THINNER

(Contd. of page 5)

111-76-2 2-butoxyethanol

BMGV	240 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: butoxyacetic acid
------	---

- **Additional information:** The lists valid during the making were used as basis.
- **Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.03.2024

Version number 2.0 (replaces version 1.0)

Revision: 11.03.2024

Trade name: Mr. RAPID THINNER

(Contd. of page 6)

· Eye/face protection



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Physical state

Fluid

· Colour:

Clear

· Odour:

Solvent-like

· Odour threshold:

Not determined.

· Melting point/freezing point:

Undetermined.

· Boiling point or initial boiling point and boiling range

78.3 °C

· Flammability

Highly flammable.

· Lower and upper explosion limit

· Lower:

Not determined.

· Upper:

Not determined.

· Flash point:

5.2 °C

· Auto-ignition temperature:

240 °C (111-76-2 2-butoxyethanol)

· Decomposition temperature:

Not determined.

· pH

Mixture is non-polar/aprotic.

· Viscosity:

· Kinematic viscosity

Not determined.

· Dynamic:

Not determined.

· Solubility

· water:

Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value)

Not determined.

· Vapour pressure:

Not determined.

· Density and/or relative density

· Density at 20 °C:

0.85–1 g/cm³

· Relative density

Not determined.

· Bulk density:

850–1,000 kg/m³

· Vapour density

Not determined.

· Other information

· Appearance:

· Form:

Fluid

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.03.2024

Version number 2.0 (replaces version 1.0)

Revision: 11.03.2024

Trade name: Mr. RAPID THINNER

(Contd. of page 7)

· **Important information on protection of health and environment, and on safety.**

- **Ignition temperature:**
- **Explosive properties:**

Product is not selfigniting.

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- **Solvent content:**

- **Organic solvents:**

110.0 %

- **VOC (EC)**

110.00 %

- **Change in condition**

- **Evaporation rate**

Not determined.

· **Information with regard to physical hazard classes**

- **Explosives**

Void

- **Flammable gases**

Void

- **Aerosols**

Void

- **Oxidising gases**

Void

- **Gases under pressure**

Void

- **Flammable liquids**

Highly flammable liquid and vapour.

- **Flammable solids**

Void

- **Self-reactive substances and mixtures**

Void

- **Pyrophoric liquids**

Void

- **Pyrophoric solids**

Void

- **Self-heating substances and mixtures**

Void

- **Substances and mixtures, which emit flammable gases in contact with water**

Void

- **Oxidising liquids**

Void

- **Oxidising solids**

Void

- **Organic peroxides**

Void

- **Corrosive to metals**

Void

- **Desensitised explosives**

Void

10 Stability and reactivity

- **Reactivity** No further relevant information available.

- **Chemical stability**

- **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

- **Possibility of hazardous reactions** No dangerous reactions known.

- **Conditions to avoid** No further relevant information available.

- **Incompatible materials:** No further relevant information available.

(Contd. on page 9)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.03.2024

Version number 2.0 (replaces version 1.0)

Revision: 11.03.2024

Trade name: Mr. RAPID THINNER

(Contd. of page 8)

· **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Harmful if inhaled.

· **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral	LD50	3,392 mg/kg
Dermal	LD50	8,000 mg/kg (rab)
Inhalative	LC50/4 h	15.4–24.5 mg/l (ATE)

78-93-3 butanone

Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)

108-10-1 4-methylpentan-2-one

Oral	LD50	2,080 mg/kg (rat)
Dermal	LD50	16,000 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (ATE) 8.3–16.6 mg/l (rat)

71-36-3 butan-1-ol

Oral	LD50	790 mg/kg (rat)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4 h	8,000 mg/l (rat)

64-17-5 ethanol

Oral	LD50	7,060 mg/kg (rat)
Inhalative	LC50/4 h	20,000 mg/l (rat)

111-76-2 2-butoxyethanol

Oral	LD50	1,200 mg/kg (ATE) 1,480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)
Inhalative	LC50/4 h	3 mg/l (ATE)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Carcinogenicity** Suspected of causing cancer.
- **STOT-single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.03.2024

Version number 2.0 (replaces version 1.0)

Revision: 11.03.2024

Trade name: Mr. RAPID THINNER

(Contd. of page 9)

· **Information on other hazards**

· **Endocrine disrupting properties**

78-93-3 butanone

List II

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Must not reach sewage water or drainage ditch undiluted or unneutralised.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|----------------------------------|-----------------------------|
| · UN number or ID number | UN1263 |
| · ADR, IMDG, IATA | |
| · UN proper shipping name | 1263 PAINT RELATED MATERIAL |
| · ADR | PAINT RELATED MATERIAL |
| · IMDG | Paint related material |
| · IATA | |

(Contd. on page 11)

—GB—

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.03.2024

Version number 2.0 (replaces version 1.0)

Revision: 11.03.2024

Trade name: Mr. RAPID THINNER

(Contd. of page 10)

· **Transport hazard class(es)**

· **ADR, IMDG, IATA**



· **Class**

3 Flammable liquids.

· **Label**

3

· **Packing group**

· **ADR, IMDG, IATA**

II

· **Environmental hazards:**

Not applicable.

· **Special precautions for user**

Warning: Flammable liquids.

· **Hazard identification number (Kemler code):** 33

· **EMS Number:**

F-E, S-E

· **Stowage Category**

B

· **Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **Transport category**

2

· **Tunnel restriction code**

D/E

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN 1263 PAINT RELATED MATERIAL, 3, II

—GB—

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.03.2024

Version number 2.0 (replaces version 1.0)

Revision: 11.03.2024

Trade name: Mr. RAPID THINNER

(Contd. of page 11)

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- EUH066 Repeated exposure may cause skin dryness or cracking.

- **Department issuing SDS:** Hobby Department
- **Contact:** -

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.03.2024

Version number 2.0 (replaces version 1.0)

Revision: 11.03.2024

Trade name: Mr. RAPID THINNER

(Contd. of page 12)

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**

GB