

Page 1/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: Mr. OXIDE RED SURFACER (Aerosol)
- · Article number: B-525
- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

GSI EUROPE - Import + Export GmbH

Louise-Dumont-Str. 31 40211 DÜSSELDORF

GERMANY

- · Further information obtainable from: Hobby Department
- · Emergency telephone number: During normal opening times: +49/211/1665 98420

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



health hazard

Carc. 2 H351 Suspected of causing cancer.



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)



Page 2/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. OXIDE RED SURFACER (Aerosol)

(Contd. of page 1)

· Hazard pictograms







GHS02 GHS05 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

butan-1-ol

4-methylpentan-2-one

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H318 Causes serious eye damage. Suspected of causing cancer. H351

· Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container in accordance with local/regional/national/international P501 regulations.

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

- Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 115-10-6 dimethyl ether		>25–≤50%	
EINECS: 204-065-8	♦ Flam. Gas 1A, H220; Press. Gas (Comp.), H280		
0, 10	butan-1-ol	10%	
EINECS: 200-751-6	♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336		
		ontd on page 3)	

(Contd. on page 3)



Page 3/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. OXIDE RED SURFACER (Aerosol)

		(Contd. of page 2
CAS: 108-10-1 EINECS: 203-550-1	4-methylpentan-2-one Flam. Liq. 2, H225; Carc. 2, H351; Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 ATE: LC50/4 h inhalative: 11 mg/l	_ 10%
CAS: 123-42-2 EINECS: 204-626-7	4-hydroxy-4-methylpentan-2-one	- 10%
CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	>2.5–≤10%
CAS: 64-17-5 EINECS: 200-578-6	ethanol Flam. Liq. 2, H225	>2.5–≤10%
CAS: 67-63-0 EINECS: 200-661-7	propan-2-ol Flam. Liq. 2, H225;	>2.5-<10%
CAS: 78-93-3 butanone Flam. Liq. 2, H225;		>2.5-<10%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	>2.5–≤10%
CAS: 108-94-1 EINECS: 203-631-1		
CAS: 141-78-6 EINECS: 205-500-4	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	>2.5-<10%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

GB



Page 4/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. OXIDE RED SURFACER (Aerosol)

(Contd. of page 3)

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Precautions for safe handling Open and handle receptacle with care.
- Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

GB



Page 5/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. OXIDE RED SURFACER (Aerosol)

(Contd. of page 4)

	rol parameters dients with limit values that require monitoring at the workplace:	
	0-6 dimethyl ether	
	Short-term value: 958 mg/m³, 500 ppm	
VV LL	Long-term value: 766 mg/m³, 400 ppm	
71-36	i-3 butan-1-ol	
	Short-term value: 154 mg/m³, 50 ppm	
	Sk	
108-1	0-1 4-methylpentan-2-one	
WEL	Short-term value: 416 mg/m³, 100 ppm	
	Long-term value: 208 mg/m³, 50 ppm	
	Sk, BMGV	
	2-2 4-hydroxy-4-methylpentan-2-one	
WEL	Short-term value: 362 mg/m³, 75 ppm	
400.0	Long-term value: 241 mg/m³, 50 ppm	
	66-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm	
64 17	/-5 ethanol	
_	Long-term value: 1920 mg/m³, 1000 ppm	
	B-0 propan-2-ol	
	Short-term value: 1250 mg/m³, 500 ppm	
VV CL	Long-term value: 1250 mg/m³, 400 ppm	
78-93	3-3 butanone	
	Short-term value: 899 mg/m³, 300 ppm	
	Long-term value: 600 mg/m³, 200 ppm	
	Sk, BMGV	
108-6	5-6 2-methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m³, 100 ppm	
	Long-term value: 274 mg/m³, 50 ppm	
400.0	Sk	
	04-1 cyclohexanone	
vv⊨L	Short-term value: 82 mg/m³, 20 ppm Long-term value: 41 mg/m³, 10 ppm	
	Sk, BMGV	
141-7	'8-6 ethyl acetate	
WEL	<u> </u>	
	Long-term value: 734 mg/m³, 200 ppm	



Page 6/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. OXIDE RED SURFACER (Aerosol)

	(Contd. of page 5)
· Ingred	lients with biological limit values:
108-10	9-1 4-methylpentan-2-one
BMGV	20 µmol/L Medium: urine Sampling time: post shift Parameter: 4-methylpentan-2-one
78-93-	3 butanone
BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one
108-94	-1 cyclohexanone
BMGV	2 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: cyclohexanol

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 7)

Page 7/14

(Contd. of page 6)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. OXIDE RED SURFACER (Aerosol)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

 Eye/face protection Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Aerosol
Red
Solvent-like
Not determined.
Undetermined.

· Boiling point or initial boiling point and boiling

range -23-6 °C

· Flammability Not applicable.

Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined.

· Flash point: -27.2 °C

Decomposition temperature: Not determined.

• **pH** Mixture is non-polar/aprotic.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

· Solubility

· water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value) Not determined.
 Vapour pressure: Not determined.

· Density and/or relative density

Density at 20 °C: 0.95–1 g/cm³
 Relative density Not determined.
 Bulk density: 950–1,000 kg/m³
 Vapour density Not determined.

(Contd. on page 8)



Page 8/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. OXIDE RED SURFACER (Aerosol)

(Contd. of page 7)

· Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health

and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• **Explosive properties:** Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

• Organic solvents: 90.0 % • VOC (EC) 90.00 %

Change in condition

· Evaporation rate Not applicable.

· Information with regard to physical hazard

classes

· Explosives Void · Flammable gases Void

• **Aerosols** Extremely flammable aerosol. Pressurised

container: May burst if heated.

· Oxidising gases Void · Gases under pressure Void · Flammable liquids Void Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void **Pyrophoric solids** Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit

flammable gases in contact with water
Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives
Void
Void
Void

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 9)



Page 9/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. OXIDE RED SURFACER (Aerosol)

(Contd. of page 8)

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	values rel	evant for classification:					
ATE (Acu	te Toxicity	y Estimates)					
Oral	LD50	7,900 mg/kg (rat)					
Inhalative	LC50/4 h	83–166 mg/l (ATE)					
	115-10-6 dimethyl ether						
Inhalative	LC50/4 h	308 mg/l (rat)					
71-36-3 bi	utan-1-ol						
Oral	LD50	790 mg/kg (rat)					
Dermal	LD50	3,400 mg/kg (rabbit)					
Inhalative	LC50/4 h	8,000 mg/l (rat)					
108-10-1	-methylp	entan-2-one					
Oral	LD50	2,080 mg/kg (rat)					
Dermal	LD50	16,000 mg/kg (rab)					
Inhalative	LC50/4 h	11 mg/l (ATE)					
		8.3–16.6 mg/l (rat)					
123-42-2	-hydroxy	-4-methylpentan-2-one					
Oral	LD50	4,000 mg/kg (rat)					
Dermal	LD50	13,630 mg/kg (rab)					
123-86-4 r	n-butyl ac	etate					
Oral	LD50	13,100 mg/kg (rat)					
Dermal	LD50	>5,000 mg/kg (rabbit)					
Inhalative	LC50/4 h	>21 mg/l (rat)					
64-17-5 et	hanol						
Oral	LD50	7,060 mg/kg (rat)					
Inhalative	LC50/4 h	20,000 mg/l (rat)					
67-63-0 pi	opan-2-o						
Oral	LD50	5,045 mg/kg (rat)					
Dermal	LD50	12,800 mg/kg (rabbit)					
Inhalative	LC50/4 h	30 mg/l (rat)					
		(Contd. on page 10)					

GB



Page 10/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. OXIDE RED SURFACER (Aerosol)

		(Contd. of page			
78-93-3 butanone					
Oral LD50 3,300 mg/kg (rat)		3,300 mg/kg (rat)			
Dermal	LD50	5,000 mg/kg (rabbit)			
108-65-6 2-methoxy-1-methylethyl acetate					
Oral	LD50	8,532 mg/kg (rat)			
Inhalative LC50/4 h 35.7 mg/l (rat) 108-94-1 cyclohexanone					
				Oral	LD50
Dermal	LD50	948 mg/kg (rabbit)			
Inhalative LC50/4 h 8,000 mg/l (rat)		8,000 mg/l (rat)			
141-78-6	ethyl aceta	ate			
Oral	LD50	5,620 mg/kg (rabbit)			
Inhalative LC50/4 h 1,600 mg/l (rat)					
		ation Causes skin irritation.			
		e/irritation Causes serious eye damage.			

- · Carcinogenicity Suspected of causing cancer.
- · Information on other hazards

· Endocrine disrupting properties	
78-93-3 butanone L	ist II

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.
- · Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

GE



Page 11/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. OXIDE RED SURFACER (Aerosol)

(Contd. of page 10)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

				-4			4	
И	4	ıne	no	TT.	IINT	orn	Tell	ion
						\mathbf{v}_{1}		

٠	UN	number	or ID	number
---	----	--------	-------	--------

· ADR, IMDG, IATA UN1950

· UN proper shipping name

ADR
 IMDG
 IATA
 1950 AEROSOLS
 AEROSOLS
 Aerosols, flammable

· Transport hazard class(es)

· ADR



· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



· Class 2.1 Gases.

· Label 2.1

· Packing group

· ADR, IMDG, IATA not regulated

• Environmental hazards: Not applicable.

· Special precautions for user Warning: Gases.

Hazard identification number (Kemler code): -

· **EMS Number:** F-D,S-U

Stowage Code SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1

(Contd. on page 12)



Page 12/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. OXIDE RED SURFACER (Aerosol)

	(Contd. of page
Segregation Code	litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of cla 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of cla 2.
Maritime transport in bulk according instruments	y to IMO Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
Transport category Tunnel restriction code	2 D
IMDG Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

(Contd. on page 13)

Page 13/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. OXIDE RED SURFACER (Aerosol)

(Contd. of page 12)

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eve damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- · Department issuing SDS: Hobby Department
- · Contact: -

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

(Contd. on page 14)



Page 14/14

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. OXIDE RED SURFACER (Aerosol)

(Contd. of page 13)

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.