

Page 1/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: Mr. FINISHING SURFACER 1500 (GREY) (Aerosol)
- · Article number: B-527
- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

GSI EUROPE - Import + Export GmbH

Louise-Dumont-Str. 31 40211 DÜSSELDORF

GERMANY

- · Further information obtainable from: Hobby Department
- · Emergency telephone number: During normal opening times: +49/211/1665 98420

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



health hazard

Carc. 2 H351 Suspected of causing cancer.



Eye Dam. 1 H318 Causes serious eye damage.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)



Page 2/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. FINISHING SURFACER 1500 (GREY) (Aerosol)

(Contd. of page 1)

· Hazard pictograms







GHS02 GHS05 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

4-methylpentan-2-one

butan-1-ol

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H318 Causes serious eye damage. H351 Suspected of causing cancer.

· Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. P210

No smoking.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous compor	nents:	
CAS: 115-10-6	dimethyl ether	>50–≤100%
EINECS: 204-065-8	🚸 Flam. Gas 1A, H220; Press. Gas (Comp.), H280	
	4-methylpentan-2-one	>10-<20%
EINECS: 203-550-1	Flam. Liq. 2, H225; & Carc. 2, H351; Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	
	ATE: LC50/4 h inhalative: 11 mg/l	Contd. on page 3)

(Contd. on page 3)

Page 3/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. FINISHING SURFACER 1500 (GREY) (Aerosol)

		Contd. of page 2)
CAS: 78-93-3	butanone	10%
EINECS: 201-159-0	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	
CAS: 64-17-5	ethanol	>2.5–≤10%
EINECS: 200-578-6	♦ Flam. Liq. 2, H225	
CAS: 71-36-3	butan-1-ol	≥3–<10%
EINECS: 200-751-6	♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	
CAS: 107-98-2	1-methoxy-2-propanol	>2.5–≤10%
EINECS: 203-539-1	♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	
CAS: 123-86-4	n-butyl acetate	>2.5–≤10%
	♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336, EUH066	
Additional information	tion: For the wording of the listed hazard phrases refer to section 16.	

4 First aid measures

- Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



Page 4/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. FINISHING SURFACER 1500 (GREY) (Aerosol)

(Contd. of page 3)

· Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Precautions for safe handling Open and handle receptacle with care.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Control parameters

Sk, BMGV

Control parameters	
Ingredients with limit values that require monitoring at the workplace:	
115-10-6 dimethyl ether	
WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm	
108-10-1 4-methylpentan-2-one	
WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm Sk, BMGV	
78-93-3 butanone	
WEL Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm	

(Contd. on page 5)



Page 5/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. FINISHING SURFACER 1500 (GREY) (Aerosol)

		(Contd. of pag
64-17	7-5 ethanol	
WEL	Long-term value: 1920 mg/m³, 1000 ppm	
71-36	6-3 butan-1-ol	
WEL	Short-term value: 154 mg/m³, 50 ppm Sk	
107-9	98-2 1-methoxy-2-propanol	
WEL	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk	
123-8	86-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm	
Ingre	edients with biological limit values:	
108-1	10-1 4-methylpentan-2-one	
BMG	SV 20 μmol/L Medium: urine Sampling time: post shift Parameter: 4-methylpentan-2-one	
78-93	3-3 butanone	
BMG	70 μmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one	

- Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- · Hand protection



(Contd. on page 6)



Page 6/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. FINISHING SURFACER 1500 (GREY) (Aerosol)

(Contd. of page 5)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Aerosol
Grey
Solvent-like
Not determined.
Undetermined.

· Boiling point or initial boiling point and boiling

range -23.6 °C Not applicable.

· Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: -32.6 °C

Decomposition temperature: Not determined.

• pH Mixture is non-polar/aprotic.

Viscosity:

Kinematic viscosity Dynamic: Not determined. Not determined.

Solubility

· water: Fully miscible.

(Contd. on page 7)



Page 7/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. FINISHING SURFACER 1500 (GREY) (Aerosol)

	(Contd. of page
Partition coefficient n-octanol/water (log va	lue) Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	0.9–1 g/cm³
Relative density	Not determined.
Bulk density:	900–1,000 kg/m³
Vapour density	Not determined.
Other information	
Appearance:	
Form:	Aerosol
Important information on protection of heal	th
and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
Solvent content:	,
Organic solvents:	100.0 %
VOC (EC)	100.00 %
Change in condition	
Evaporation rate	Not applicable.
Information with regard to physical hazard	
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised
	container: May burst if heated.
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	•
	Void
tlammable gases in contact with water	
flammable gases in contact with water Oxidising liquids	Void
Oxidising liquids	Void Void
	Void Void Void

(Contd. on page 8)



Page 8/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. FINISHING SURFACER 1500 (GREY) (Aerosol)

(Contd. of page 7)

Desensitised explosives

Void

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	values rele	evant for classification:
ATE (Acu	te Toxicity	y Estimates)
Oral	LD50	15,800 mg/kg (rat)
Inhalative	LC50/4 h	55.3–111 mg/l (ATE)
115-10-6	dimethyl e	ther
Inhalative	LC50/4 h	308 mg/l (rat)
108-10-1	1-methylp	entan-2-one
Oral	LD50	2,080 mg/kg (rat)
Dermal	LD50	16,000 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (ATE)
		8.3–16.6 mg/l (rat)
78-93-3 bi	utanone	
Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)
64-17-5 et	hanol	
Oral	LD50	7,060 mg/kg (rat)
Inhalative	LC50/4 h	20,000 mg/l (rat)
71-36-3 bi	utan-1-ol	
Oral	LD50	790 mg/kg (rat)
Dermal	LD50	3,400 mg/kg (rabbit)
		(Contd. on page 9)

(Contd. on page 9)



Page 9/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. FINISHING SURFACER 1500 (GREY) (Aerosol)

		(Contd. of page 8)
Inhalative	LC50/4 h	8,000 mg/l (rat)
107-98-2 1	-methoxy	-2-propanol
Oral	LD50	5,660 mg/kg (rat)
Dermal	LD50	13,000 mg/kg (rabbit)
123-86-4 r	n-butyl ac	etate
Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

- · Serious eye damage/irritation Causes serious eye damage.
- · Carcinogenicity Suspected of causing cancer.
- · Information on other hazards

· Endocrine disrupting properties	
78-93-3 butanone	List II

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 10)

GB.



Page 10/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. FINISHING SURFACER 1500 (GREY) (Aerosol)

(Contd. of page 9)

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

UN number or ID number ADR, IMDG, IATA	UN1950	
UN proper shipping name		
ADR	1950 AEROSOLS	
IMDG IATA	AEROSOLS Aerosols, flammable	
	Aerosois, nammable	
Transport hazard class(es)		
ADR		
Class	2 5F Gases.	
Label	2.1	
IMDG, IATA		
Class	2.1 Gases.	
Label	2.1	
Packing group ADR, IMDG, IATA	not regulated	
Environmental hazards:	Not applicable.	
Special precautions for user Hazard identification number (Kemle	Warning: Gases.	
EMS Number:	F-D,S-U	

GB



Page 11/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. FINISHING SURFACER 1500 (GREY) (Aerosol)

	(Contd. of page
Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of a litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
Maritima transport in bulk according	
Maritime transport in bulk according instruments	Not applicable.
instruments	
instruments Transport/Additional information:	
instruments Transport/Additional information: ADR	
instruments Transport/Additional information: ADR Limited quantities (LQ)	Not applicable.
Instruments Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category	Not applicable. 1L Code: E0
	Not applicable. 1L Code: E0 Not permitted as Excepted Quantity 2
Instruments Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code	Not applicable. 1L Code: E0 Not permitted as Excepted Quantity 2
instruments Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG	Not applicable. 1L Code: E0 Not permitted as Excepted Quantity 2 D

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

(Contd. on page 12)

Page 12/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. FINISHING SURFACER 1500 (GREY) (Aerosol)

(Contd. of page 11)

· Reportable explosives precursors

None of the ingredients is listed.

Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.

EUH066 Repeated exposure may cause skin dryness or cracking.

- · Department issuing SDS: Hobby Department
- · Contact: -

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

(Contd. on page 13)



Page 13/13

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024 Version number 2.0 (replaces version 1.0) Revision: 07.06.2024

Trade name: Mr. FINISHING SURFACER 1500 (GREY) (Aerosol)

(Contd. of page 12)

ATE: Acute toxicity estimate values

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

* Data compared to the previous version altered.