

Page 1/12

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 3.0 (replaces version 2.0)

Revision: 07.06.2024

1 Identification of the substance/mixture and of the company/undertaking

- Product identifier
- · Trade name: AQUEOUS White Surfacer 1000 (jar type)
- · Article number: HSF-02
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Coating
- Details of the supplier of the safety data sheet
 Manufacturer/Supplier: GSI EUROPE - Import + Export GmbH Louise-Dumont-Str. 31 40211 DÜSSELDORF GERMANY
- · Further information obtainable from: Hobby Department
- · Emergency telephone number: During normal opening times: +49/211/1665 98420

2 Hazards identification

Classification of the substance or mixture
 Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB



Page 2/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 07.06.2024

Printing date 07.06.2024

Version number 3.0 (replaces version 2.0)

Trade name: AQUEOUS White Surfacer 1000 (jar type)

Hazard n	ictograms (Contd. of page 1
	\wedge
<u> (19</u>)	
	\mathbf{V}
GHS02	GHS07
Signal w	ord Danger
Hazard-d	letermining components of labelling:
2-butoxye	ethanol
propan-2-	-ol
Hazard s	tatements
H225	Highly flammable liquid and vapour.
H312+H3	32 Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
	onary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
	No smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P303+P3	61+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with
	water [or shower].
P305+P3	51+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
B / 0 =	lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/internationa regulations.
Other ha	zards
Results d	of PBT and vPvB assessment
PBT: Not	applicable.
vPvB: No	t applicable.

3 Composition/information on ingredients

Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)



Page 3/12

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 3.0 (replaces version 2.0)

Revision: 07.06.2024

Trade name: AQUEOUS White Surfacer 1000 (jar type)

	(0	Contd. of page 2)
 Dangerous compo 	nents:	
CAS: 67-63-0 EINECS: 200-661-7	propan-2-ol Flam. Liq. 2, H225; () Eye Irrit. 2, H319; STOT SE 3, H336	≥20–≤25%
CAS: 111-76-2 EINECS: 203-905-0	2-butoxyethanol ♦ Acute Tox. 3, H311; Acute Tox. 3, H331; ♦ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE: LD50 oral: 1,200 mg/kg LC50/4 h inhalative: 3 mg/l	>10–≤25%
CAS: 107-98-2 EINECS: 203-539-1	1-methoxy-2-propanol Flam. Liq. 3, H226; () STOT SE 3, H336	>2.5–≤10%
CAS: 64-17-5 EINECS: 200-578-6	ethanol 🚸 Flam. Liq. 2, H225	>2.5–≤10%
CAS: 78-83-1 EINECS: 201-148-0	butanol	≥1–≤2.5%
• Additional informa	tion: For the wording of the listed hazard phrases refer to section 16.	

4 First aid measures

- Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing: If symptoms persist consult doctor.

- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 4)



Page 4/12

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 3.0 (replaces version 2.0)

Revision: 07.06.2024

Trade name: AQUEOUS White Surfacer 1000 (jar type)

- (Contd. of page 3) • Special hazards arising from the substance or mixture No further relevant information available. • Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:
 Dilute with plenty of water.
 Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.
- Ensure adequate ventilation.
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- **Information about fire and explosion protection:** Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
 Specific end use(s) No further relevant information available.

(Contd. on page 5)

GP



Page 5/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 3.0 (replaces version 2.0)

Revision: 07.06.2024

Trade name: AQUEOUS White Surfacer 1000 (jar type)

(Contd. of page 4)

Control parameters Ingredients with limit values that require monitoring at the workplace: 67-63-0 propan-2-ol 67-63-0 propan-2-ol WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm 111-76-2 2-butoxyethanol 111-76-2 2-butoxyethanol WEL Short-term value: 246 mg/m³, 50 ppm Long-term value: 123 mg/m³, 25 ppm Sk, BMGV 107-98-2 1-methoxy-2-propanol 107-98-2 1-methoxy-2-propanol WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk 64-17-5 ethanol 102 pterm value: 1920 mg/m³, 1000 ppm WEL Long-term value: 1920 mg/m³, 1000 ppm WEL Long-term value: 1920 mg/m³, 1000 ppm WEL Long-term value: 1920 mg/m³, 1000 ppm	
67-63-0 propan-2-ol WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm 111-76-2 2-butoxyethanol WEL Short-term value: 246 mg/m³, 50 ppm Long-term value: 123 mg/m³, 25 ppm Sk, BMGV 107-98-2 1-methoxy-2-propanol WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk 64-17-5 ethanol WEL Long-term value: 1920 mg/m³, 1000 ppm 78-83-1 butanol	
WELShort-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm111-76-2 2-butoxyethanolWELShort-term value: 246 mg/m³, 50 ppm Long-term value: 123 mg/m³, 25 ppm Sk, BMGV107-98-2 1-methoxy-2-propanolWELShort-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk64-17-5 ethanolWELLong-term value: 1920 mg/m³, 1000 ppm78-83-1 butanol	
Long-term value: 999 mg/m³, 400 ppm 111-76-2 2-butoxyethanol WEL Short-term value: 246 mg/m³, 50 ppm Long-term value: 123 mg/m³, 25 ppm Sk, BMGV 107-98-2 1-methoxy-2-propanol WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk 64-17-5 ethanol WEL Long-term value: 1920 mg/m³, 1000 ppm 78-83-1 butanol	
WEL Short-term value: 246 mg/m³, 50 ppm Long-term value: 123 mg/m³, 25 ppm Sk, BMGV 107-98-2 1-methoxy-2-propanol WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk 64-17-5 ethanol WEL Long-term value: 1920 mg/m³, 1000 ppm 78-83-1 butanol	
Long-term value: 123 mg/m³, 25 ppm Sk, BMGV 107-98-2 1-methoxy-2-propanol WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk 64-17-5 ethanol WEL Long-term value: 1920 mg/m³, 1000 ppm 78-83-1 butanol	
WEL Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk 64-17-5 ethanol WEL Long-term value: 1920 mg/m³, 1000 ppm 78-83-1 butanol	
Long-term value: 375 mg/m³, 100 ppm Sk 64-17-5 ethanol WEL Long-term value: 1920 mg/m³, 1000 ppm 78-83-1 butanol	
WEL Long-term value: 1920 mg/m³, 1000 ppm 78-83-1 butanol	
78-83-1 butanol	
WEL Short-term value: 231 mg/m ³ , 75 ppm Long-term value: 154 mg/m ³ , 50 ppm	
Ingredients with biological limit values:	
111-76-2 2-butoxyethanol	
BMGV 240 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: butoxyacetic acid	
Additional information: The lists valid during the making were used as basis.	
Exposure controls Appropriate engineering controls No further data; see section 7. Individual protection measures, such as personal protective equipment General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or long	ger
exposure use self-contained respiratory protective device. (Contd.	on page



Page 6/12

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 3.0 (replaces version 2.0)

Revision: 07.06.2024

(Contd. of page 5)

GB

Trade name: AQUEOUS White Surfacer 1000 (jar type)

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye/face protection



Tightly sealed goggles

9 Physica	l and chemica	I properties

 Information on basic physical and chemica 	al properties	
General Information		
 Physical state 	Fluid	
· Colour:	White	
· Odour:	Solvent-like	
· Odour threshold:	Not determined.	
 Melting point/freezing point: 	Undetermined.	
Boiling point or initial boiling point and bo	iling	
range	78 °C (64-17-5 ethanol)	
· Flammability	Highly flammable.	
Lower and upper explosion limit		
Lower:	1.1 Vol %	
· Upper:	~19 Vol %	
· Flash point:	22 °C	
Auto-ignition temperature:	238 °C	
Decomposition temperature:	Not determined.	
		(Contd. on page 7)



Page 7/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 3.0 (replaces version 2.0)

Revision: 07.06.2024

Trade name: AQUEOUS White Surfacer 1000 (jar type)

	(Contd. of page
рН	Mixture is non-polar/aprotic.
Viscosity:	
Kinematic viscosity at 40 °C	>20.5 mm²/s
Dynamic:	Not determined.
Solubility	
water:	Fully miscible.
Partition coefficient n-octanol/water (log value) Not determined.
Vapour pressure at 20 °C:	58 hPa
Density and/or relative density	
Density at 20 °C:	~1.123 g/cm³
Relative density	Not determined.
Bulk density:	~1,123 kg/m³
Vapour density	Not determined.
Other information	
Appearance:	
Form:	Fluid
Important information on protection of health	
and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
Solvent content:	
Organic solvents:	56.0 %
Water:	25.0 %
VOC (EC)	56.00 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard	
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	v ora
flammable gases in contact with water	Void
Oxidising liquids	Void

GB



Page 8/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 07.06.2024

Printing date 07.06.2024

Version number 3.0 (replaces version 2.0)

Trade name: AQUEOUS White Surfacer 1000 (jar type)

		(Contd. of page 7)
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
 Desensitised explosives 	Void	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Harmful in contact with skin or if inhaled.

 LD/LC50 values relevant for classificatio 	n:
---	----

ATE (Acu	-	/ Estimates)
Oral	LD50	6,000 mg/kg (ATE)
	LD50	6,000 mg/kg (ATE) 2,000 mg/kg (rab)
Inhalative	LC50/4 h	15 mg/l (ATE)

67-63-0 pi	ropan-2-o	
Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)
111-76-2 2	2-butoxye	thanol
Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)
Inhalative	LC50/4 h	3 mg/l (ATE)
107-98-2 ²	I-methoxy	r-2-propanol
Oral	LD50	5,660 mg/kg (rat)
Dermal	LD50	13,000 mg/kg (rabbit)
		(Contd. on page 9)

- GB



Page 9/12

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 3.0 (replaces version 2.0)

Revision: 07.06.2024

Trade name: AQUEOUS White Surfacer 1000 (jar type)

		(Contd. of page a
64-17-5 e	thanol	
Oral	LD50	7,060 mg/kg (rat)
Inhalative	LC50/4 h	20,000 mg/l (rat)
78-83-1 b	utanol	
Oral	LD50	2,460 mg/kg (rat)
Dermal	LD50	3,400 mg/kg (rabbit)
Skin corr	osion/irrit	ation Causes skin irritation.
Serious e	∍ye damag	e/irritation Causes serious eye irritation.
STOT-sir	igle expos	ure May cause drowsiness or dizziness.
Informati	ion on othe	er hazards

information on other nazarus

Endocrine disrupting properties

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 10)



Page 10/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 3.0 (replaces version 2.0)

Revision: 07.06.2024

Trade name: AQUEOUS White Surfacer 1000 (jar type)

(Contd. of page 9)

• **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

UN number or ID number ADR, IMDG, IATA	UN1263
UN proper shipping name	
ADR IMDG	1263 PAINT RELATED MATERIAL
IATA	PAINT RELATED MATERIAL Paint related material
Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
Packing group	
ADR, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	
EMS Number:	F-E, <u>S-E</u>
Stowage Category	В
Maritime transport in bulk according to IMO	
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
Transport astagony	Maximum net quantity per outer packaging: 500 ml
Transport category Tunnel restriction code	2 D/E



Page 11/12

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 Printing date 07.06.2024

Version number 3.0 (replaces version 2.0)

Revision: 07.06.2024

Trade name: AQUEOUS White Surfacer 1000 (jar type)

(Contd. of page 10)

 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture · Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.

(Contd. on page 12)

GB



Page 12/12

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 07.06.2024

Version number 3.0 (replaces version 2.0)

Revision: 07.06.2024

Trade name: AQUEOUS White Surfacer 1000 (jar type)

(Contd. of page 11) H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. Department issuing SDS: Hobby Department · Contact: -· Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative ATE: Acute toxicity estimate values Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 * * Data compared to the previous version altered.