Page 1/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024 Version number 3.0 (replaces version 2.0) Revision: 04.06.2024

## 1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

· Trade name: Mr. BASE WHITE

· Article number: SF-283

Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

GSI EUROPE - Import + Export GmbH

Louise-Dumont-Str. 31 40211 DÜSSELDORF

**GERMANY** 

- · Further information obtainable from: Hobby Department
- · Emergency telephone number: During normal opening times: +49/211/1665 98420

#### 2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

Carc. 2 H351 Suspected of causing cancer.



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)



Page 2/12

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 3.0 (replaces version 2.0) Revision: 04.06.2024 Printing date 04.06.2024

Trade name: Mr. BASE WHITE

· Hazard pictograms

(Contd. of page 1)









GHS02 GHS05 GHS07

#### · Signal word Danger

### · Hazard-determining components of labelling:

4-methylpentan-2-one

butan-1-ol

#### · Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H351 Suspected of causing cancer.

H336 May cause drowsiness or dizziness.

#### · Precautionary statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse. P362+P364

Store locked up. P405

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Other hazards

#### · Results of PBT and vPvB assessment

· **PBT:** Not applicable. vPvB: Not applicable.

## 3 Composition/information on ingredients

- Mixtures
- · **Description**: Mixture of substances listed below with nonhazardous additions.

· Dangerous compon	ents:	
	4-methylpentan-2-one	>25–≤50%
	Flam. Liq. 2, H225;  Carc. 2, H351;  Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 ATE: LC50/4 h inhalative: 11 mg/l	
	(C	contd. on page 3)



Page 3/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024 Version number 3.0 (replaces version 2.0) Revision: 04.06.2024

Trade name: Mr. BASE WHITE

		(Contd. of page 2)
CAS: 64-17-5	ethanol	>2.5–≤10%
EINECS: 200-578-6	♦ Flam. Liq. 2, H225	
CAS: 71-36-3	butan-1-ol	10%
EINECS: 200-751-6	♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	
CAS: 123-42-2	4-hydroxy-4-methylpentan-2-one	10%
EINECS: 204-626-7	Flam. Liq. 3, H226;  Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 10 %	
CAS: 78-93-3	butanone	>2.5-<10%
EINECS: 201-159-0	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	
CAS: 123-86-4	n-butyl acetate	>2.5–≤10%
EINECS: 204-658-1	♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336, EUH066	
CAS: 141-78-6	ethyl acetate	>2.5-<10%
EINECS: 205-500-4	♠ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	

Additional information: For the wording of the listed hazard phrases refer to section 16.

#### 4 First aid measures

- Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

#### 5 Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)



Page 4/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024 Version number 3.0 (replaces version 2.0) Revision: 04.06.2024

Trade name: Mr. BASE WHITE

(Contd. of page 3)

- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

GB



Page 5/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024 Version number 3.0 (replaces version 2.0) Revision: 04.06.2024

Trade name: Mr. BASE WHITE

(Contd. of page 4)

	rol parameters dients with limit values that require monitoring at the workplace:
108-1	0-1 4-methylpentan-2-one
WEL	Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm Sk, BMGV
64-17	-5 ethanol
WEL	Long-term value: 1920 mg/m³, 1000 ppm
71-36	-3 butan-1-ol
WEL	Short-term value: 154 mg/m³, 50 ppm Sk
	2-2 4-hydroxy-4-methylpentan-2-one
WEL	Short-term value: 362 mg/m³, 75 ppm Long-term value: 241 mg/m³, 50 ppm
78-93	-3 butanone
WEL	Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV
123-8	6-4 n-butyl acetate
WEL	
141-7	8-6 ethyl acetate
WEL	Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm
Ingre	dients with biological limit values:
108-1	0-1 4-methylpentan-2-one
BMG\	V 20 μmol/L Medium: urine Sampling time: post shift Parameter: 4-methylpentan-2-one
78-93	-3 butanone
BMG\	V 70 μmol/L Medium: urine Sampling time: post shift

- · **Additional information:** The lists valid during the making were used as basis
- · Exposure controls
- · Appropriate engineering controls No further data; see section 7.

(Contd. on page 6)

Page 6/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024 Version number 3.0 (replaces version 2.0) Revision: 04.06.2024

Trade name: Mr. BASE WHITE

(Contd. of page 5)

#### · Individual protection measures, such as personal protective equipment

#### General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

#### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

#### 9 Physical and chemical properties

- Information on basic physical and chemical properties
- · General Information
- · Physical state

1 Hysical state

· Colour:

· Odour:

· Odour threshold:

Fluid

White Solvent-like

Not determined.

(Contd. on page 7)



Page 7/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024 Version number 3.0 (replaces version 2.0) Revision: 04.06.2024

Trade name: Mr. BASE WHITE

(Contd. of page 6)

• Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

range 76.5 °C

· Flammability Highly flammable.

· Lower and upper explosion limit

Lower: 1.2 Vol %
Upper: 19 Vol %
Flash point: 16.4 °C
Auto-ignition temperature: 345 °C

• Decomposition temperature: Not determined.

• **pH** Mixture is non-polar/aprotic.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C: 120 hPa

Density and/or relative density

Density at 20 °C: 0.9–1.2 g/cm³
 Relative density Not determined.
 Bulk density: 900–1,200 kg/m³
 Vapour density Not determined.

· Other information

· Appearance:

· Form: Fluid

· Important information on protection of health

and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

Organic solvents: 75.0 %
 Water: 15.0 %
 VOC (EC) 75.00 %

Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard

classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void

(Contd. on page 8)



Page 8/12

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024 Version number 3.0 (replaces version 2.0) Revision: 04.06.2024

Trade name: Mr. BASE WHITE

		(Contd. of page 7)
· Gases under pressure	Void	
Flammable liquids	Highly flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
· Organic peroxides	Void	
Corrosive to metals	Void	
<ul> <li>Desensitised explosives</li> </ul>	Void	

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values relevant for classification:	
ATE (Acu	te Toxicity	/ Estimates)
Oral	LD50	7,900 mg/kg (rat)
Inhalative	LC50/4 h	20.8–41.5 mg/l (ATE)
108-10-1	4-methylp	entan-2-one
Oral	LD50	2,080 mg/kg (rat)
Dermal	LD50	16,000 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (ATE)
		8.3–16.6 mg/l (rat)
	•	(Contd. on page 9



- IMPORT + EXPORT GMBH

Page 9/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024 Version number 3.0 (replaces version 2.0) Revision: 04.06.2024

Trade name: Mr. BASE WHITE

		(Contd. of p
64-17-5 et	hanol	
Oral	LD50	7,060 mg/kg (rat)
Inhalative	LC50/4 h	20,000 mg/l (rat)
71-36-3 bi	utan-1-ol	
Oral	LD50	790 mg/kg (rat)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4 h	8,000 mg/l (rat)
123-42-2	1-hydroxy	-4-methylpentan-2-one
Oral	LD50	4,000 mg/kg (rat)
Dermal	LD50	13,630 mg/kg (rab)
78-93-3 bi	utanone	
Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)
123-86-4 ı	n-butyl ac	etate
Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)
141-78-6	ethyl aceta	ate
Oral	LD50	5,620 mg/kg (rabbit)
Inhalative	LC50/4 h	1,600 mg/l (rat)

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye damage.
- · Carcinogenicity Suspected of causing cancer.
- STOT-single exposure May cause drowsiness or dizziness.
- Information on other hazards

· Endocrine disrupting properties	
78-93-3 butanone	List II

## 12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.
- · Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

(Contd. on page 10)



Page 10/12

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024 Version number 3.0 (replaces version 2.0) Revision: 04.06.2024

Trade name: Mr. BASE WHITE

(Contd. of page 9)

- · Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage

Must not reach sewage water or drainage ditch undiluted or unneutralised.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

-	4				4 .			400
и	<i>1</i>	rar	1 e r	nor	• 1	ntc	rma	tion
	-			лол	ш н	1114	71 11 (4)	14 FATE

IIN mumbar on ID mumbar	
· UN number or ID number · ADR, IMDG, IATA	UN1263
· UN proper shipping name	
· ADR	1263 PAINT RELATED MATERIAL
· IMDG	PAINT RELATED MATERIAL
· IATA	Paint related material
T	

- Transport hazard class(es)
- · ADR, IMDG, IATA



· Class 3 Flammable liquids. · Label 3

· Packing group

· ADR, IMDG, IATA Ш

· Environmental hazards: Not applicable.

· Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code): 33

· EMS Number: F-E,S-E

(Contd. on page 11)



Page 11/12

# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024 Version number 3.0 (replaces version 2.0) Revision: 04.06.2024

Trade name: Mr. BASE WHITE

Stowage Category	В
Maritime transport in bulk accordin	g to IMO
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
,	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
·IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
, , , , , , , , , , , , , , , , , , , ,	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, II

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

GB



Page 12/12

## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.06.2024 Version number 3.0 (replaces version 2.0) Revision: 04.06.2024

Trade name: Mr. BASE WHITE

(Contd. of page 11)

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

EUH066 Repeated exposure may cause skin dryness or cracking.

#### · Department issuing SDS: Hobby Department

· Contact: -

#### Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

\* Data compared to the previous version altered.

GB